

1 Identification

- · Product identifier
- · Trade name: Heavy Cut Compound 1000
- · Article number: 22984
- · Application of the substance / the mixture Abrasive and polishing compound
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:
- Menzerna Polishing Compounds GmbH & Co. KG Industriestraße 25 76470 ÖTIGHEIM GERMANY sds@menzerna.com
- · Information department: Product and Environmental Safety Department
- · Emergency telephone number: +49 (0) 761 19240 (24 h)

2 Hazard(s) identification

· Classification of the substance or mixture The product is not classified according to the Globally Harmonized System (GHS).

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC Not applicable.

- · Label elements
- · GHS label elements Void
- Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · Classification system:
- · NFPA ratings (scale 0 4)



· HMIS-ratings (scale 0 - 4)

HEALTH Health = 0 FIRE 1 Fire = 1 **REACTIVITY** Reactivity = 0

- · Other hazards
- Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:			
1344-28-1	aluminium oxide	25-50%	
64742-48-9	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics Xn R65 R66 ♦ Asp. Tox. 1, H304; Flam. Liq. 4, H227	10-<25%	
	(Co	ntd. on page 2)	

Page 1/7

US -

Reviewed on 07/30/2015

Printing date 07/30/2015

Reviewed on 07/30/2015

Trade name: Heavy Cut Compound 1000

		Contd. of page 1)
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic	2.5-<10%
	🗞 Asp. Tox. 1, H304	-
61791-28-4	alcohols, tallow, ethoxylated	2.5-<10%
	🗙 Xi R38; 🌄 N R50	
	🚯 Skin Irrit. 2, H315	_
68439-49-6	Alcohols, C16-18, ethoxylated (>5-<15 EO)	0.1-≤2.5%
	🗙 Xn R22; 🗙 Xi R36; 🌄 N R50	
	Acute Tox. 4, H302; Eye Irrit. 2A, H319	_
56-81-5	glycerol	0.1-≤2.5%

4 First-aid measures

- · Description of first aid measures
- General information: No special measures required.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing:

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

- Information for doctor:
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- Indication of any immediate medical attention and special treatment needed Treat according to symptoms.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: Water spray, foam, dry powder or carbon dioxide.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture Nitrogen oxides (NOx)
- Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device. Wear fully protective suit.

6 Accidental release measures

• **Personal precautions, protective equipment and emergency procedures** Keep unnecessary personnel away. Ensure adequate ventilation. Use personal protection recommended in section 8.

• Environmental precautions: Do not allow to enter sewers/ surface or ground water.

• Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

• **Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

US -

polishing compounds

Printing date 07/30/2015

polishing compounds

Reviewed on 07/30/2015

Trade name: Heavy Cut Compound 1000

(Contd. of page 2)

7 Handling and storage

- · Handling:
- · Precautions for safe handling No special precautions are necessary if used correctly.
- Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:
- Store in a well-ventilated place. Storage temperature: between 15 °C and 25 °C.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

Control parameters

· Com	· Components with limit values that require monitoring at the workplace:		
1344-	1344-28-1 aluminium oxide		
PEL	Long-term value: 15*; 15** mg/m³ *Total dust; ** Respirable fraction		
REL	Long-term value: 10* 5** mg/m³ as Al*Total dust**Respirable/pyro powd./welding f.		
TLV	Long-term value: 1* mg/m³ as Al; *as respirable fraction		
64742	64742-56-9 Distillates (petroleum), solvent-dewaxed light paraffinic		
TWA	Long-term value: 5 mg/m ³		
56-81	56-81-5 glycerol		
PEL	Long-term value: 15* 5** mg/m³ mist; *total dust **respirable fraction		
TLV	TLV withdrawn-insufficient data human occup. exp.		

• Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
- · General protective and hygienic measures:
- The usual precautionary measures for handling chemicals should be followed.
- · Breathing equipment: Not necessary if room is well-ventilated.
- · Protection of hands:

Protective gloves are recommended.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. of page 3)

Safety Data Sheet acc. to OSHA HCS

Reviewed on 07/30/2015

Trade name: Heavy Cut Compound 1000

polishing compounds

Printing date 07/30/2015

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Safety glasses

• Body protection: Protective work clothing

· Information on basic physical and chemical properties			
· General Information			
· Appearance:			
Form:	Fluid		
Color:	White		
· Odor:	Characteristic		
· Odour threshold:	Not determined.		
· pH-value at 20 °C (68 °F):	> 7		
· Change in condition			
Melting point/Melting range:	Undetermined.		
Boiling point/Boiling range:	> 100 °C (> 212 °F)		
· Flash point:	> 100 °C (> 212 °F)		
· Flammability (solid, gaseous):	Not applicable.		
· Decomposition temperature:	Not determined.		
· Auto igniting:	Product is not selfigniting.		
· Danger of explosion:	Product does not present an explosion hazard.		
· Density at 20 °C (68 °F):	1.45 g/cm³ (12.1 lbs/gal)		
· Relative density	Not determined.		
· Vapour density	Not determined.		
· Evaporation rate	Not determined.		
· Solubility in / Miscibility with			
Water:	Partly miscible.		
· Partition coefficient (n-octanol/wate	r): Not determined.		
· Viscosity:			
Dynamic:	Not determined.		
Kinematic at 40 °C (104 °F):	> 20.5 mm²/s		
· Solvent content:			
VOC content:	12.3 %		
	266.7 g/l / 2.23 lb/gl		
· Other information	No further relevant information available.		

* 10 Stability and reactivity

· Reactivity None under normal conditions.

- · Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.

Printing date 07/30/2015

polishing compounds

Reviewed on 07/30/2015

Trade name: Heavy Cut Compound 1000

(Contd. of page 4)

· Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:

64742-48-9 Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

- Oral LD50 >5000 mg/kg (rat)
- Dermal LD50 >3000 mg/kg (rab)

Primary irritant effect:

- on the skin: No irritant effect.
- · on the eye: No irritating effect.
- Sensitization: No sensitizing effects known.
- · Additional toxicological information:

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

* 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

• Other adverse effects No further relevant information available.

* 13 Disposal considerations

- · Waste treatment methods
- Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Must be specially treated adhering to official regulations.

· Waste disposal key:

Waste codes should be determined in consultation with the customer, supplier and disposal.

· Uncleaned packagings:

• Recommendation: Disposal must be made according to official regulations.

14 Transport information

· UN-Number

· DOT, ADR, ADN, IMDG, IATA

Void

Printing date 07/30/2015

polishing compounds

Reviewed on 07/30/2015

Trade name: Heavy Cut Compound 1000

		(Contd. of page 5)
 UN proper shipping name DOT, ADR, ADN, IMDG, IATA 	Void	
 Transport hazard class(es) 		
· DOT, ADR, ADN, IMDG, IATA · Class	Void	
 Packing group DOT, ADR, IMDG, IATA 	Void	
 Environmental hazards: Marine pollutant: 	No	
· Special precautions for user	Not applicable.	
 Transport in bulk according to Anne MARPOL73/78 and the IBC Code 	c II of Not applicable.	
· UN "Model Regulation":	-	

* 15 Regulatory information

 Safety, health and environmental regulations/legislation specific for the substance or mixture Regulation 1907/2006/EC, REACH concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals. Regulation 453/2010/EU, REACH as amended. Regulation 1272/2008/EC, on Classification, Labelling and Packaging of substances and mixtures. Sara 		
· Section 355 (extremely hazardous substances):		
None of the ingredients is listed.		
· Section 313 (Specific toxic chemical listings):		
1344-28-1 aluminium oxide		
TSCA (Toxic Substances Control Act):		
All ingredients are listed.		
· Proposition 65		
· Chemicals known to cause cancer:		
None of the ingredients is listed.		
· Chemicals known to cause reproductive toxicity for females:		
None of the ingredients is listed.		
· Chemicals known to cause reproductive toxicity for males:		
None of the ingredients is listed.		
· Chemicals known to cause developmental toxicity:		
None of the ingredients is listed.		
· Carcinogenic categories		
· EPA (Environmental Protection Agency)		
None of the ingredients is listed.		
· TLV (Threshold Limit Value established by ACGIH)		
1344-28-1aluminium oxideA4		
NIOSH-Ca (National Institute for Occupational Safety and Health)		
None of the ingredients is listed.		

(Contd. on page 7)

⁻ US -

Printing date 07/30/2015

Reviewed on 07/30/2015

Trade name: Heavy Cut Compound 1000

(Contd. of page 6)

- · GHS label elements Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H227 Combustible liquid.

H302 Harmful if swallowed.

- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.

H319 Causes serious eye irritation.

- R22 Harmful if swallowed.
- R36 Irritating to eyes.
- R38 Irritating to skin.
- R50 Very toxic to aquatic organisms.
- R65 Harmful: may cause lung damage if swallowed.
- R66 Repeated exposure may cause skin dryness or cracking.
- Department issuing SDS: Product and Environmental Safety Department
- Date of preparation / last revision 07/30/2015 / 21
- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

- IMDG: International Maritime Code for Dangerous Goods
- DOT: US Department of Transportation
- IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

- EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- NFPA: National Fire Protection Association (USA)
- HMIS: Hazardous Materials Identification System (USA)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- Flam. Liq. 4: Flammable liquids, Hazard Category 4
- Acute Tox. 4: Acute toxicity, Hazard Category 4
- Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
- Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A
- Asp. Tox. 1: Aspiration hazard, Hazard Category 1

* * Data compared to the previous version altered.

menzerna polishing compounds